

VEGA 10

IP-rated downlight

design Roberto Mantovani



IP67 recessed luminaires that offer the highest build quality; with extremely small dimensions; elevated luminous fluxes and embedded optics for high visual comfort. The body and front are of thick anodised aluminium; with powder coating on the face. Extra-clear tempered glass; ATEX cable gland and neoprene cable. Available in a range of colour temperatures and beam apertures.

Encastrables trimless IP67 de très haute qualité constructive; avec des dimensions extrêmement contenues. Corps en aluminium anodisé à épaisseur; versions avec frontal en aluminium anodisé et peint en poudre. Verre extra-clair trempé; presse-étoupe ATEX; câble en néoprène. L'optique en retrait garantit un confort visuel élevé.

Luminarias empotrables trimless IP67 de muy alta calidad de fabricación con tamaño extremadamente reducido. Cuerpo de aluminio anodizado con espesor; versiones con frente de aluminio anodizado y barnizado con polvo. Vidrio templado extra claro; prensaestopas ATEX; cable de neoprene. La óptica hacia atrás garantiza un alto confort visual.



IP67

Class 2



made in Canada

Supply current

Courant d'alimentation
Corriente de alimentación

Static White: 500mA (V_i18V)

Dim To Warm: 400mA (V_i18V)

Power

Pouissance
Potencia

Static White: 9W

Dim To Warm: 7,2W

Series wiring

Câblage en série
Cableado en serie

LED selection

Sélection des LED
Selección del LED

2-Step MacAdam

CRI

98

Lumens

2400K — 770 lm

2700K — 1125 lm

3000K — 1180 lm


3500K — 1195 lm

4000K — 1178 lm

DW — 667 lm

Dimensions


Dimensiones



Photometric diagrams

Diagrammes photométriques

Diagramas fotométricos



Code construction

Construction du code produit

Construcción del código de producto

VG1 X X X

N	S	M	W	X
15°	24°	36°	60°	120°
B	N	C		
White	Black	Custom		
24	27	30	35	40
2400K	2700K	3000K	3500K	4000K
				DW
				Dim to Warm

Accessories

Accessoires

Accesorios

AT086R02060

Airtight recessed housing for insulated ceiling

IC086R02060

Recessed housing for insulated ceiling

LH04

Low luminance hex louvre

MP-R060




Baseplate

R02060

T-bar baseplate

CSXJ01

Recessing box



Static White 500mA drivers

Static White Alimentateurs 500mA

Static White Alimentadores 500mA

CCPR010A-500 (1) IP20

Dimming: PHASE - 0-10V

CCPR040A-500 (1..3) IP20

Dimming: PHASE - 0-10V

Dim to Warm 400mA drivers

Dim to Warm Alimentateurs 400mA

Dim to Warm Alimentadores 400mA

CCPR010A-400 (1) IP20

Dimming: PHASE - 0-10V

CCPR040A-400 (1..3) IP20

Dimming: PHASE - 0-10V